

This material has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

## IP 2518

This vinyl has been specifically designed for printing with all solvent and UV inks. It can be used only on flat surfaces and is intended for indoor and outdoor applications. IP 2518 has a double-sided, PE-coated backing paper, which offers excellent layflat properties. Laminate: IP 2810-100 or IP 2810-101 or ImagePerfect™ water-based liquid laminate with UV protection.

Specifications	
DESCRIPTION	Intermediate Vinyl
COLOUR	White Gloss
FACE FILM THICKNESS	70μ
WEIGHT	N/A
ADHESIVE	Solvent acrylic, permanent
ADHESIVE STRENGTH	20N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 140g / m <sup>2</sup>
TEMPERATURE RANGE	-30°C to +90°C
DURABILITY (UNPRINTED)	Up to 5 years
FLAME RETARDANCY	Adhered to steel, self-extinguishing
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© June 2008 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.